

Tool

Pistol Tools

Model	Torque Range		Max. Speed (rpm)		*Weight		Length		Battery Pack Included	Drive Mode
	N·m	ft·lb	25V Battery	36V Battery	kg	lb	mm	in		
EHC2-R3008-PW1	1.6-8	1.2-5.9	1100	1500					BPL-2520ES	Direct / Pulse
EHC2-R3015-PW1	3-15	2.2-11.1	600	800	1.4	3.1	224	8.8		
EHC2-T3030-PW1	6-30	4.4-22.1	1100	1500						
EHC2-T3050-PW1	10-50	7.4-36.9	1000	1350	1.65	3.6	233	9.2		

*Note: Weight does not include the battery.

Right Angle Tools

Model	Torque Range		Max. Speed	*Weight		Length		Battery Pack Included	Drive Mode
	N·m	ft·lb	rpm	kg	lb	mm	in		
EHC2-R1030-AW1	6-30	4.4-22.1	393	2.3	5.1	517	20.4	BPL-3620ES	Direct
EHC2-R1050-AW1	10-50	7.4-36.9	215	2.6	5.7	532	20.9		
EHC2-R1065-AW1	13-65	9.6-47.9	166	2.9	6.4	564	22.2		
EHC2-R1090-AW1	18-90	13.3-66.4	117	3.5	7.7	598	23.5		Pulse
EHC2-T0020-AW1	4-20	3.0-14.8	1029	2.0	4.4	489	19.3		
EHC2-T0040-AW1	8-40	5.9-29.5	844	2.4	5.3	503	19.8		
EHC2-T0070-AW1	14-70	10.3-51.6	581	2.7	6.0	531	20.9		
EHC2-T2100-AW1	20-100	14.8-73.8	608	3.2	7.1	567	22.3		

*Note: Weight does not include the battery.

Wireless Communication Specifications

Communication Method	WLAN
Frequency Band	2.4GHz / 5GHz
Security Method	WEP (64bit, 128bit), WPA-PSK, WPA2-PSK

AIM Kit (Optional)

LCD Display and Barcode Scanner



- Tool Unit Information Display
- Tightening Result and Error Display
- Barcode and QR Code Reading
- Channel and Job Selection, etc.

Model Number	Tool Unit Model + AIM Kit (ex. EHC2-R3008-PW1+AIM2) (ex. EHC2-R3008-AW1+AIM2)
Barcode Symbology	Barcode (CODE 39, 128; etc.) QR Code, Data Matrix Code
Display Size	1.5 inch LCD (240x240 dots)
Buttons	Up, Down, Left, Right, Set
Weight	130g

Battery Pack

Model	Voltage	Ampere-hour	Weight		Compatibility
			kg	lb	
BPL-2510ES	DC25.2V	1.0Ah	0.40	0.88	Pistol Tools
BPL-2520ES	DC25.2V	2.0Ah	0.54	1.19	Pistol Tools
BPL-3610ES	DC36V	1.0Ah	0.47	1.04	Right Angle & Pistol
BPL-3620ES	DC36V	2.0Ah	0.68	1.50	Right Angle & Pistol

Battery Charger

Model	Applicable Battery	Rated Input	Rated Output	Charging Time
BC2075MX	BPL-2510ES	AC100-240V 50/60Hz	2.0A±0.2A	45 min.
	BPL-2520ES		2.0A±0.2A	75 min.
	BPL-3610ES		1.6A±0.2A	50 min.
	BPL-3620ES		1.6A±0.2A	90 min.

MIF

Up to 10 WiFi tools can be connected and controlled via WLAN access points.




Max No. of Channel	250	Fieldbus	Model
Max No. of Job	99 (30 Steps/Job)	Standard Spec	EHC2-MIF10-N
Storage Capacity	Fastening Results : 100,000/1Workstation Torque Curve : 1,000/1Workstation System Error : 1,000	CC-Link	EHC2-MIF10-M
		PROFINET	EHC2-MIF10-S
		EtherNet/IP	EHC2-MIF10-R
DC Output Power	DC24V Max. 1.5A		
Power Supply	Single Phase AC100~230V 50/60Hz		

Management Software

EHC2-MIF-PC

Exclusive management software designed for the Master Interface Unit (MIF), featuring a range of capabilities including parameter reading and writing, data storage management, monitoring of tightening results, overlaying torque curves, displaying cursor coordinates, and managing I/O allocation.

Languages : Japanese, English, Chinese, Korean
OS : Windows 11, Windows 10



Data Logger

ESW-DL

Dedicated software designed to automatically log tightening data through Ethernet connection. The acquired data, including torque waveforms, are sequentially recorded in a database, and presented on the screen. Additionally, batch output can be scheduled and set with the acquired tightening results prepared in CSV or Excel file formats, facilitating a streamlined generation of reports.



ESTIC CORPORATION

1-2-16 Togodori, Moriguchi-city,
Osaka, 570-0041 Japan



JP : www.estic.co.jp

EN : www.estic-global.com

CN : www.cn.estic-global.com

YouTube www.youtube.com/user/EsticCorporation

LinkedIn www.linkedin.com/company/estic-corporation



ESTIC



Optimize Manufacturing Processes
with Advanced Industry 4.0 Tools


Cordless Nutrunner

Handy 2000 Cordless 2



Introducing the Next Generation

The expanded memory and improved communication performance enable smooth fastening operations while maintaining high-precision fastening quality during communication with the MIF or a host PC. Fastening results can be stored in the tool's internal memory.



The tool has a built-in control/driver which provides feedback control every half millisecond. Even with wireless operation, high tightening accuracy equivalent to that of a wired nutrunner can be achieved.

Convenient Display and Barcode Scanner

The AIM kit (optional) has a 1.5-inch display that allows a user to quickly check fastening status. Easily link workpiece serials with fastening results and select fastening programs from barcode data.




Connect Up to 10 Tools

Pair up to 10 tools to a single MIF controller and effortlessly manage the connected tools and tightening data. Create up to 250 fastening programs with ease.



5GHz and 2.4GHz Compatibility


The MIF Controller offers WLAN support in both 5GHz and 2.4GHz frequencies. Our lightning-fast MIF series transmits results to the PC software in just few seconds. Select network configurations for an interference-free operation.



Significantly Reduce Reaction Torque

A Breakthrough in Operator Safety

Our pioneering Pulse Technology introduces a solution for minimizing operator strain. Instead of continuous momentum, which creates a large reaction force, our Pulse Technology breaks the force up into fractions of a second by acting like a hammer making small taps. The user receives little reaction force in response and the system records torque data every 1/2000th of a second for a precise approach. As a result, you can achieve safe and accurate tightening.



Collect and Report Result Data to a Host Server

